

Fanless Embedded PC System With Lowest Dimensions and Intel's ATOM Technology



Features

Processor

- Intel Atom Z530 with 1.6 GHz (Hyper Threading)
- 533 MHz FSB
- 512 kB L2 cache

Memory

- System memory 1 GB DDR2
- Internal ATA SSD 4 GB
- Battery-free NVRAM 128 kB
- Internal CFast Socket for SATA SSD

Video

- Intel Graphics Media Accelerator 500 (Intel GMA 500)
- Up to 256 MB frame buffer supporting Direct X 9.0E and Open GL 2.0
- DVI-D graphic interface on front panel (Single Link)
- Single channel LVDS on internal connector

Expansion

- iX-Bus 8/16 bit interface for I/O and low speed peripherals

Front Panel Connectors

- 1 x 10/100/1000 Mbit/s Ethernet,
- 1 x 10/100 Mbit/s Ethernet
- 3 x USB (V 2.0), with 500 mA power supply capability
- 2 x 9-pin D-SUB connectors for CAN or serial ports
version /0: 2 x RS232 serial interface or
version /1: 1 x CAN and 1 x RS232 or
version /2: 2 x CAN interface
- Serial port with RTS/CTS only
- Reset push button
- Status LED for power supply status

CAN

- SJA 1000 CAN Controller
- Physical Layer ISO/DIS 11898-2, isolated from logic
- Bus termination is software switchable, 120 Ω resistor

Power Supply

- Input 9..32 V DC
- Power consumption max. 12 W

Physical

- Ambient operating temperature 0 °C ... 50 °C
- Non-operating temperature range from -20 °C ... 75 °C
- Humidity 0 % ~ 80 %, non-condensing
- Dimensions (w x h x d): 111 x 62 x 104 mm
- Weight approx. 0.8 kg

Options

- CoDeSys IEC61131-3 runtime environment
- 1.1 GHz version is optionally

Supported Operating Systems

WES 7, Windows XP / XPe, Windows CE 6.0, Linux, QNX, other operating systems on request...

For special Windows CE images contact your regional sales office.

Fanless Embedded PC System With Lowest Dimensions and Intel's ATOM Technology



Ordering Information

emPC-X1600/0 SY-EPC-70001

- Intel ATOM with 1.6 GHz and 1 GB DDR2, 4 GB SSD, 2 x RS232 ports

emPC-X1600/1 SY-EPC-70000

- Intel ATOM with 1.6 GHz and 1 GB DDR2, 4 GB SSD, 1 x CAN/CANopen port, 1 x RS232 port

emPC-X1600/2 SY-EPC-70002

- Intel ATOM with 1.6 GHz and 1 GB DDR2, 4 GB SSD, 2 x CAN/CANopen ports

CompactFlashes, operating system images and other options have to be ordered separately. Please contact the Janz Tec offices!



The emPC-X1600 systems are also available as embedded Panel PC with display size from 6.5" up to 15.0".

Contact Information

Janz Tec AG
Im Doerener Feld 8
33100 Paderborn
Germany

Phone +49.52 51.15 50.100
Fax +49.52 51.15 50.190
E-Mail sales@janztec.com
Web www.janztec.com