

ATOM Based Embedded Panel PC System With 12.1 inch Display Size



Features

Housing

- Aluminum front panel with front foil for corporate design (standard is Janz Tec' design)
- Dimensions of complete emVIEW-12T (w x h x d): 320 x 260 x 101 mm (Version /1, /2) (w x h x d): 320 x 260 x 118 mm (Version /4)
- Display cut-out dimensions (w x h): 300 x 240 mm
- Weight approx. 3.6 kg

Display

- 12.1" (30.7 cm) SVGA TFT LCD display
- Resolution 800 x 600
- Contrast ratio 700:1 (typ.)
- Luminance 450 cd/m² (typ.)
- LED backlight for high reliability

Touchscreen

- Resistive 4-wire Touchscreen

Computing System

Processor

- Intel Atom Z530 with 1.6 GHz (Hyper Threading);
- 533 MHz FSB
- 512 kB L2 cache

Memory

- System memory 1 GB DDR2
- Internal ATA SSD 4 GB
- Battery-free nvSRAM 128 kB

Video

- Intel Graphics Media Accelerator 500 (Intel GMA 500)
- Up to 256 MB frame buffer supporting Direct X 9.0E and Open GL 2.0
- DVI-D graphic interface on front panel (Single Link)
- Single channel LVDS on internal connector

Interfaces

- 1 x 10/100/1000 Mbit/s Ethernet, 1 x 10/100 Mbit/s Ethernet
- 3 x USB (V 2.0), with 500 mA power supply capability
- 2 x 9-pin D-SUB connectors for CAN or serial ports
version /1: 1 x CAN/CANopen and 1 x RS232 or
version /2: 2 x CAN/CANopen interfaces, w/o RS232
- Reset push button
- Status LEDs

CAN/CANopen

- SJA 1000 CAN Controller
- Physical Layer ISO/DIS 11898-2, isolated from logic
- Bus termination is software switchable, 120 Ω resistor

Internal Expansion

- iX-Bus 8/16 bit interface for I/O and low speed peripherals

Power Supply

- Input 14..32 V DC
- Power consumption TBD

Physical

- Ambient operating temperature 0 °C...45 °C
- Non-operating temperature range from -20 °C...75 °C
- Humidity 0 % ~ 80 %, non-condensing

Options

- CoDeSys IEC61131-3 runtime environment

Supported Operating Systems

Windows XPembedded, Windows CE 6.0, WES 7, Linux, QNX, other operating systems on request...

ATOM Based Embedded Panel PC System With 12.1 inch Display Size



Ordering Information

emVIEW-12T/X1600/1

SY-EMV-71120

- emVIEW-12T/X1600, based on standard emPC-X1600/1
1 CAN port; 1 x RS232 port

emVIEW-12T/X1600/2

SY-EMV-71121

- emVIEW-12T/X1600, based on standard emPC-X1600/2
2 CAN ports

emVIEW-12T/X1600/R3

SY-EMV-71125


- emVIEW-12T/X1600, based on standard emPC-X1600/R3
1 CAN port; 3 x RS232 ports

emVIEW-12T/X1600/1-IO

SY-EMV-71126

- emVIEW-12T/X1600, based on standard emPC-X1600/1-IO
1 CAN port; 1 x RS232, 8 x digital IO; 4 x analog Inputs;
4 x analog Outputs

Windows images and other options have to be ordered separately. Please contact the Janz Tec offices!



Contact Information

Janz Tec AG
Im Doererer Feld 8
33100 Paderborn
Germany

Phone +49.52 51.15 50.0
Fax +49.52 51.15 50.190
E-Mail sales@janztec.com
Web www.janztec.com