

Fanless SlimLine Embedded Panel PC System With 8.4 inch Display Size



Features

Housing

- Aluminum front panel with front foil for corporate design (standard is Janz Tec' design)
- Dimensions of complete emVIEW-8T (w x h x d): 257 x 190 x 45 mm (Version /0, /1, /2) (w x h x d): 257 x 190 x 62 mm (Version /R3)
- Display cut-out dimensions (w x h): 233 x 165 mm
- Weight approx. 1.6 kg

Display

- 8.4" (21.3 cm) SVGA TFT LCD display
- Resolution 800 x 600
- Contrast ratio 370:1 (500 typ.)
- Luminance 400 cd/m² (typ.)
- LED backlight for high reliability

Touchscreen

- Resistive 4-wire Touchscreen

Computing System

Processor

- ARM Cortex A8: Freescale i.MX515 with 600 MHz
- 2 x 32 kB L1 cache, 256 kB L2 cache
- Vector floating point co-processor

Memory

- System memory 256 MB DDR2-RAM
- NVRAM 32 kB (battery free solution)
- Internal storage medium Compact Flash socket, Type I/II

Video

- OpenGL® ES2.0 and OpenVGTM 1.1 accelerator
- 24 bit display support up to WXGA resolution

Clocks and Timers

- Timekeeper (TOY); part of the NVRAM, requires battery
- Watchdog timer

Interfaces

- 2 x 9-pin D-SUB connectors for CAN or serial ports
version /0: 2 x RS232 serial interface or
version /1: 1 x CAN and 1 x RS232 or
version /2: 2 x CAN/CANopen interface
- 2 x 10/100 Mbit/s Ethernet
- 2 x USB (V 2.0), with 500 mA power supply capability
- 15-pin D-SUB VGA port
- Receptacle for power supply
- Reset push button
- Status LED for power supply status

CAN/CANopen

- SJA 1000 CAN Controller
- Physical Layer ISO/DIS 11898-2, isolated from logic
- Bus termination is software switchable, 120 Ω resistor

Internal Expansion

- iX-Bus 8/16 bit interface for I/O and low speed peripherals

Power Supply

- Input 9...32 V DC
- Power consumption < 10 W

Physical

- Ambient operating temperature 0 °C...60 °C
- Non-operating temperature range -20 °C...75 °C
- Humidity 0 % ~ 80 %, non-condensing

Options

- CoDeSys IEC61131-3 runtime environment
- Extended operating temperature range -20 °C...60 °C

Supported Operating Systems

Windows CE 6.0, Linux; other operating systems on request...
For special Windows CE images contact your regional Janz Tec sales office.

Fanless SlimLine Embedded Panel PC System With 8.4 inch Display Size



Ordering Information

emVIEW-8T/A500/0 **SY-EMV-51082**

- emVIEW-8T/A500, based on standard emPC-A500/0
2 x RS232 ports

emVIEW-8T/A500/1 **SY-EMV-51080**

- emVIEW-8T/A500, based on standard emPC-A500/1
1 x CAN port; 1 x RS232 port

emVIEW-8T/A500/2 **SY-EMV-51081**

- emVIEW-8T/A500, based on standard emPC-A500/2
2 x CAN ports

emVIEW-8T/A500/R3 **SY-EMV-51085**

- emVIEW-8T/A500, based on standard emPC-A500/1
1 x CAN port; 3 x RS232 ports

emVIEW-8T/A500/1-IO **SY-EMV-51086**


- emVIEW-8T/A500, based on standard emPC-A500/1-IO
1 x CAN port; 1 x RS232 port, 8 x digital IO,
4 x analog Inputs, 4 x analog Outputs

emVIEW-8/A500 **SY-EMV-50086**

- Same systems as above, but without resistive touchscreen

CompactFlashes, Windows CE images and other options
have to be ordered separately.

Please contact the Janz Tec offices!



Contact Information

Janz Tec AG
Im Doerener Feld 8
33100 Paderborn
Germany

Phone +49.52 51.15 50.100
Fax +49.52 51.15 50.190
E-Mail sales@janztec.com
Web www.janztec.com