

Round plug connector 7/8"




Connection cable
7/8" - 7/8"

Male
straight

Female
straight

Male
90°


Female
90°



Approvals:

1	Form	No.	50021		50051	
	Suppression		5-pole		5-pole	
	Circuit diagram		Power cable		Power cable	
	Contact layout					
2	Cable type	Jacket color			Jacket color	
	Wire diameter		gray		gray	
	PUR (UL/CSA-listed)		961		961	
3	Cable length					
	0.3 m	0030				
	0.6 m	0060				
	1.0 m	0100				
	1.5 m	0150				
	2.0 m	0200				
	Your article no.					
	The composition of your article number is explained on page 1.1.2	7000 — — Murrelektronik Standard				
		1 Form 2 Cable type 3 Cable length				
Notes		Accessories and technical data in chapter 1.10. Further cable lengths on request.				

**Female
straight**



Approvals: 

Round plug connector 7/8"

Round plug connector 7/8"





Connection cable
7/8" - 7/8"

Male
straight

Female
straight



Approvals:



1	Form	No.	50041		
	Suppression	5-pole			
		Bus cable, shielded			
	Circuit diagram				
2	Contact layout				
	Cable type	Jacket color			
	Wire diameter		gray		
	PVC (Data AWG 18/Power AWG 15)		952		
3	Cable length				
	0.3 m	0030			
	0.6 m	0060			
	1.0 m	0100			
	1.5 m	0150			
	2.0 m	0200			
	Your article no.				
	The composition of your article number is explained on page 1.1.2	7000 Murrelektronik Standard - -			
		1	Form	2	Cable type
		3	Cable length		
Notes		Accessories and technical data in chapter 1.10. Further cable lengths on request.			

Round plug connector 7/8"

Connection cable
7/8" - 7/8"

T-coupler
Male, straight to
Female, straight



1	Form	No.	50061		
Suppression/Circuit diagram		5-pole			
		Male 1. Female 			
Contact layout		Male Female 			
Technical data					
Supply voltage		50 V AC/DC			
Current per contact		max. 8 A			
Protection		IP67 when plugged and screwed down (EN 60529)			
Temperature range		-20...+80 °C			
Your article no.					
The composition of your article number is explained on page 1.1.2		7000 — — — — 000 0000 Murrelektronik Standard			
		1 Form			
Notes					

Accessories and technical data in chapter 1.10.
Further cable lengths on request.

Round plug connector 7/8"





Connection cable
7/8" - 7/8"

Bus-Terminator
DeviceNet, CANopen

DeviceNet
CANopen
Approvals:



1	Form	No.	78301			
	Suppression/Circuit diagram	5-pole				
	Contact layout					
	Technical data					
	Current per contact		max. 8 A			
	Connection type		screw fixing			
	Protection		IP67 when plugged and screwed down (EN 60529)			
	Temperature range		-20...+80 °C			
	Your article no.					
	The composition of your article number is explained on page 1.1.2		7000 Murrelektronik Standard	-	000	0000
			1	Form		
	Notes					
			Accessories and technical data in chapter 1.10. Further cable lengths on request.			